

## Spindle actuator EA-SU-230/300

Universal application options due to moveable mounting brackets, almost noiseless run, robust against environmental influences, cut off in both end positions by integrated limit switches, appealing design - just to mention a few of the outstanding characteristics of the modern 230 V actuator.



### Technical Data:

Spindle actuator Type EA-SU-230/300 Item number:	
Nominal voltage:	230 V AC / 50 Hz
Nominal current:	0.7 A
Stroke length:	300, 500 mm
Force:	300 N
Cut-off:	Integrated limit switches, Thermal cut off
Speed:	20 mm/s
Dimensions:	Aluminium, RAL 9010, 413 (613 mm with 500 mm stroke) x 74 x 85 mm
Ingress protection:	IP 65
Switch on duration:	ED 10 %
Connection cable:	Plastic (4-core), black, length 1.0 m
Brackets (incl.):	Standard mounting brackets
Weight:	Approx. 3.0 kg

### Article

Nominal force 300 N/0.7 A Speed with nominal load 20 mm/sec		
	Typ	Item number
	EA-SU-230/300/300	M2 1220
Attributes:	Force 300 N / 300 mm Stroke length	
	EA-SU-230/300/500	M2 1221
Attributes:	Force 300 N / 500 mm Stroke length	

### Actuator and Bracket coating

Note: Small parts as screws, nuts and sliding parts will not be coated!

Accessories	Item number
Coating in all RAL and DB colours Prices on request	